

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BSB INTENSE WHITE  
Product code : L0620000

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels  
Chemical nature : Mono compound enamel - finish coat

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : safety@lechler.eu  
Responsible/issuing person

#### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299  
This telephone number is available during office hours only. (8.00-18.00)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.

##### Classification (67/548/EEC, 1999/45/EC)

Flammable	R10: Flammable.
	R66: Repeated exposure may cause skin dryness or cracking.
	R67: Vapours may cause drowsiness and dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Hazard pictograms



Signal word

: Warning

Hazard statements

: H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements

: EUH066 Repeated exposure may cause skin dryness or cracking.  
**Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 123-86-4 n-butyl acetate
- reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene)
- Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Liquid pigmented dispersion

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
---------------	---	--------------------------------	--	----------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

xylene	1330-20-7 215-535-7 01- 2119488216- 32	R10 Xn; R20/21 Xi; R38 Nota C	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 1 - < 5
butan-1-ol	71-36-3 200-751-6 01- 2119484630- 38	R10 Xn; R22 Xi; R37/38-R41 R67	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	>= 1 - < 5
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benz	400-830-7 01- 0000015075- 76-0017	R43 N; R51/53	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,1 - < 1
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	01- 2119491304- 40-0000	R43 N; R50/53	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
Substances with a workplace exposure limit :				
titanium dioxide	13463-67-7 236-675-5 01- 2119489379- 17			>= 30 - < 50
n-butyl acetate	123-86-4 204-658-1 01- 2119485493- 29	R10 R66 R67	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 25 - < 30
1-methoxy-2-propanol	107-98-2 203-539-1 01- 2119457435- 35	R10 R67	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5 - < 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01- 2119475791- 29	R10	Flam. Liq. 3; H226	>= 1 - < 5

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.  
Seek medical advice.  
Put eye-washer on working place  
Remove contact lenses.
- If swallowed : If accidentally swallowed obtain immediate medical attention.  
Do NOT induce vomiting.  
Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.  
Seek medical advice.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Keep containers and surroundings cool with water spray.
- Unsuitable extinguishing media : Do NOT use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding of the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Thoroughly mix before using  
After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline materials.

### 7.3 Specific end use(s)

: This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
titanium dioxide (airborne, unbound particles of respirable size)	13463-67-7	TWA	10 mg/m <sup>3</sup>		ACGIH
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m <sup>3</sup>		ACGIH
		STEL	200 ppm 950 mg/m <sup>3</sup>		ACGIH
1-methoxypropan-2-ol	107-98-2	TWA	100 ppm 375 mg/m <sup>3</sup>	2000-06-16	2000/39/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	150 ppm 568 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm 550 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm 442 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
butan-1-ol	71-36-3	TWA	20 ppm		ACGIH

### DNEL

titanium dioxide

: End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Local effects  
Value: 10 mg/m3

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Specific effects  
Value: 700 ppm

n-butyl acetate

: End Use: Professional use  
Exposure routes: Skin contact  
Potential health effects: Local effects  
Exposure time: 8 h  
Value: 7 ppm

End Use: Professional use  
Exposure routes: Inhalation  
Potential health effects: Local effects  
Value: 48 mg/m3

### PNEC

titanium dioxide

: Fresh water  
Value: > 1 mg/l

Fresh water sediment  
Value: >= 1000 mg/kg

Marine water  
Value: 0,127 mg/l

Marine sediment  
Value: >= 100 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

n-butyl acetate

Soil  
Value: 100 mg/kg

: Water  
Value: 0,18 mg/l

Soil  
Value: 0,093 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.  
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.  
Respirator with combination filter for vapour/particulate (EN 141).

Hand protection : Solvent-resistant gloves (butyl-rubber)  
For prolonged or repeated contact use protective gloves.  
Protective gloves complying with EN 374.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.  
Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.  
Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire.  
Personnel should wear protective clothing.  
Workers should wear antistatic footwear.

#### Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties



# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Appearance	: liquid
Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: not applicable
pH	: not determined
Freezing point	: not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 1,3324 g/cm <sup>3</sup>
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 80 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	: not applicable
Evaporation rate	: not determined

### 9.2 Other information

Solids by weight	: 54,53 %
Volatile organic compounds (VOC) content	: 45,47 %

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None reasonably foreseeable.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.  
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : not applicable

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Product

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method  
Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method  
Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method  
Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.  
Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

#### Components:

##### **xylene :**

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

##### **butan-1-ol :**

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg, Converted acute toxicity point estimate

#### **Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate :**

Acute oral toxicity : LD50: 3.230 mg/kg, rat

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxicity to fish :  
Remarks:  
No data is available on the product itself.

Toxicity to fish  
Reaction mass of : LC50: 0,97 mg/l  
Bis(1,2,2,6,6-pentamethyl-4-  
piperidyl) sebacate and Exposure time: 96 h  
Methyl 1,2,2,6,6-  
pentamethyl-4-piperidyl Species: Lepomis macrochirus (Bluegill sunfish)  
sebacate Method: OECD Test Guideline 203  
  
LC50: 7,9 mg/l  
Exposure time: 96 h  
  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: OECD Test Guideline 203  
  
LC50: 0,9 mg/l  
Exposure time: 96 h  
  
Species: Brachydanio rerio (zebrafish)  
semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)  
Reaction mass of : NOEC: 1 mg/l  
Bis(1,2,2,6,6-pentamethyl-4-  
piperidyl) sebacate and Exposure time: 21 d  
Methyl 1,2,2,6,6- Species: Daphnia magna (Water flea)  
pentamethyl-4-piperidyl Method: OECD Test Guideline 211  
sebacate

#### 12.2 Persistence and degradability

Biodegradability : No data available

#### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

#### 12.4 Mobility in soil

Mobility : No data available

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).  
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
The following Waste Codes are only suggestions: 150110\*

---

### SECTION 14: Transport information

#### 14.1 UN number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

#### 14.2 Proper shipping name

ADR PAINT

IMDG PAINT

IATA Paint

#### 14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA : 3

#### 14.4 Packing group

ADR

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F - E,S - E

### IATA

Packing group : III  
Labels : 3

#### 14.5 Environmental hazards

##### ADR

Environmentally hazardous : no

##### IMDG

Marine pollutant : no

##### IATA

Environmentally hazardous : no

#### 14.6 Special precautions for user

Remarks : Packagings smaller or equal to 450 l, transport according to section E of marginal 2301.

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : not applicable

MAL-Code-Number (DK) : 4-3 (1993)  
1.678-m3 air/10 g

Risk classification according to VbF : Exempt  
see user defined free text

Water contaminating class : slightly water endangering

# SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

## BSB INTENSE WHITE

Version 2.21

Revision Date 07.05.2015

Print Date 14.05.2015

(Germany)

VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

The product is classified and labelled in accordance with Directive 1999/45/EC.

### 15.2 Chemical Safety Assessment

No data is available on the product itself.

---

## SECTION 16: Other information

### Full text of R-phrases referred to under sections 2 and 3

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.